

Easier and quicker drive-in of animals through newly-designed catching device and pushing gate

- head catching device takes head position into account
- adapts to animal size
- mechanic or hydraulic pushing gate, also useable as table prolongation
- crush can be opened wide at the front and side for easier exit of the animal

Simple, self-explaining operation

- distances between working steps reduced by up to 40%
- centrally positioned operating controls at an ergonomic height
- At least 30% higher working output per hour
- simple belt system with hydraulic tension

Easy transport and comfortable operation

- Less space required in the barn
- transportable with multiple means such as fork lift, lift truck or tractor
- integrated hitch-points for ground-mounting
- toolbox within easy reach
- easy to service



Easier and quicker drive-in



Best working height, tools within easy reach



Wide opening for exit to the front or side

Serial equipment

- head-catching device (open sliding door takes head position into account for easy drive-in)
- hydraulic belly belt tension
- central operating unit from working station
- closed pushing bow for quick drive-in
- 3-point-hitch cat. II, forklift support 4-sided, truck-lift device 2-sided
- High-quality Bosch-Rexroth hydraulic power-unit with 1,8 kW electric motor
- Cow comfort mat 30 mm
- 4 units of □ 40 mm leg holders with chain fastener, retensionable, rapid self-locking height adjustment
- complete belt system (for belly and legs)
- tool box with 3 plugs
- fixing points for ground mounting
- easy-accessible service windows
- complete frame galvanized

Types

- **Kipp Top II Basic:** Serial equipment
- **Kipp Top II Comfort:** additionally equipped with mechanic pushing gate and tool box (2x angle grinder, 2x knife holders)
- **Kipp Top II Professionell:** additionally equipped with hydraulic pushing gate and tool box (2x angle-grinder, 2x knife holders) and emergency device for external hydraulic (in case of power failure)
- **Kipp Top II Trailer** (Professional version)

Complementary equipment

- operation of the hydraulic pushing gate from the rear
- Set of guiding fences for hoof trimming comfort set
- Support for set of guiding fences
- Guiding fence connection
- Ground mounting set
- Toolbox
- Emergency plug for external hydraulic



Technical data

Outer dimensions: (transport dimensions)	2000/2150/2100 mm
Required space for operation:	3600 x 3700 mm (LxW)
Recommended animal size:	Withers height: up to 1750 mm Shoulder width: up to 750 mm Live weight: 300 to 1000 kg
Support/attachment:	3-point-hitch Cat II forklift support, 4-sided lift truck 2-sided
Electric supply:	230 V / 50 Hz
Transmission:	electrohydraulic 1,8 kW
Surface:	hot-zinc galvanized + powder coated
Bedding:	Rubber mat Cow comfort 30 mm



New position of leg holders, practical tool-box



3-point hitch Cat II, fork-lift and truck-lift device, hitching points for ground-mounting