

# ROSENSTEINER THREE POINT BUCKETS

EXPERIENCE THE DIFFERENCE



## Simply different

- Bolt-on scraper strip HB400
- Tilt angle 90°
- High-dump force
- Flat design for simple loading
- Excellent welded quality
- High quality powder coating

## Simply faster – simply higher

With the three-point buckets you increase the tipping height of your loader by up to 50% compared to conventional loader shovels.

## Simply unique

For everyday use from the construction site to timber transport and snow-clearing. A top product for modern farmers, for professional use by municipalities, garden centres and biomass companies.

## Load securing

The three-point bucket has six lashing points as standard. Additional uprights, Add-on side walls and lashing points guarantee a secure fastening of every load.





	<b>KENDO</b>	<b>AIKIDO</b>	<b>JUDO</b>	<b>SAMURAI</b>	<b>SUMO</b>
<b>Payload</b>	<b>1.0 t</b>	<b>2.5 t</b>	<b>2.5 t</b>	<b>3.5 t</b>	<b>5.0 t</b>
<b>Vehicle performance</b>	<b>Up to 40 hp</b>	<b>Up to 75 hp</b>	<b>Up to 75 hp</b>	<b>Up to 120 hp</b>	<b>Up to 200 hp</b>
<b>Hydraulic lifting power</b>	<b>Max. 1300 kg</b>	<b>Max. 2800 kg</b>	<b>Max. 2800 kg</b>	<b>Max. 4800 kg</b>	<b>Max. 6800 kg</b>
<b>Depth</b>	<b>80 cm</b>	<b>80 cm</b>	<b>110 cm</b>	<b>125 cm</b>	<b>125 cm</b>
<b>Width (inside)</b>	160 / 180 / 200 cm Special widths possible	160 / 180 / 200 / 220 cm Special widths possible	160 / 180 / 200 / 220 cm Special widths possible	200 / 220 / 250 / 270 / 300 cm Special widths from 160 cm possible	200 / 220 / 250 / 270 / 300 cm Special widths from 200 cm possible
<b>Side wall height to front wall height</b>	42 cm - 46 cm	42 – 46 cm	42 – 50 cm	42 – 62 cm	60 – 80 cm
<b>Three-point hitch</b>	Cat I, ∅ 22, 4-way adjustable,  Suitable for front and rear mounting	Cat II short ∅28mm, DIN= BM 680mm  Cat II ∅28mm, DIN= BM 825mm  (Cat I ∅22mm – Drilling as standard, bolts on request) Cat I front mounting for double-axle mowers, also suitable for side shift	Cat II kurz ∅28mm, DIN= BM 680mm  Cat II ∅28mm, DIN= BM 825mm  (Cat I ∅22mm – Drilling as standard, bolts on request) Cat I front mounting for double-axle mowers, also suitable for side shift	Cat II ∅28mm, DIN= BM 825mm	Cat II ∅28mm, DIN= BM 825mm Cat III short ∅36mm combined
<b>Standard equipment</b>	<ul style="list-style-type: none"> <li>• Bolt-on scraper strip (HB 400)</li> <li>• Removable tailboard</li> <li>• Two cylinder system (Sumo four cylinder system)</li> <li>• Powder-coated finish: trough RAL 3003, rear wall + three point hitch RAL 7046</li> <li>• 6 lashing points for load securing</li> <li>• Mounting holes for accessories</li> </ul>				
<b>Accessories</b>	<ul style="list-style-type: none"> <li>○ Tailboard swivel device and loading area extension</li> <li>○ Uprights (max. 6 pieces)</li> <li>○ Forklift mount</li> <li>○ Additional screwed lashing points</li> <li>○ Special painting</li> <li>○ Direct mounts</li> <li>○ Bulk attachment</li> <li>○ Drawbar lock</li> </ul>		<ul style="list-style-type: none"> <li>○ Lateral wear protection HB 400 (standard on Sumo)</li> <li>○ Screw-on plastic scraper bar</li> <li>○ Scraper bar HB 500 to screw on</li> <li>○ Stone chip protection film</li> <li>○ Tool holder</li> <li>○ Municipal package</li> <li>○ Professional package for commercial use</li> </ul>		